



LOCKING PIN
Enables a secure head closing.

CG40

HYDRAULIC CUTTING TOOL MANUAL GUILLOTINE TYPE

> Identical force, stroke and capacities as the **XCG40** and the battery operated tool **BCP040G**.

TYPE OF CABLES
copper, aluminum and steel

MAX. PASSAGE
Ø 40 mm
(depending on cables)



- NEW REINFORCED BLADES**
Increase blades life time (> especially for steel cuts).
- IDENTICAL BLADE & COUNTER BLADE**
Improve the cable cutting.
- INTERCHANGEABLE BLADES**
Easy to replace.
- 2 SPEEDS HYDRAULIC SYSTEM**
For a fast advance.

FORCE	88 kN
DIMENSIONS (L x l x h in mm)	645 x 85 x 165
WEIGHT	5.880 kg



CANVAS BAG – Delivered with the tool.

	TYPE OF CABLES	MAX. HARDNESS	MAX. Ø OF CUT (mm) *
CABLES	Copper	< 40 daN/mm ²	Ø 32 (630 mm ²)
	Aluminum	< 20 daN/mm ²	Ø 40
	Hard copper	< 34 daN/mm ²	Ø 40
	Steel	< 180 daN/mm ²	7 x Ø 3.0 (= Ø 9.0) 19 x Ø 2.1 (= Ø 10.5) 19 x Ø 2.3 (= Ø 11.5)
	Multistrands steel	< 180 daN/mm ²	Ø 18 (strands quantities: 200)
	ACSR	< 180 daN/mm ²	26 x Ø 2.50 + 7 x Ø 1.95 (= Ø 15.85) 26 x Ø 3.06 + 7 x Ø 2.38 (= Ø 19.38) 26 x Ø 3.60 + 7 x Ø 2.80 (= Ø 22.80) 54 x Ø 3.50 + 19 x Ø 2.10 (= Ø 31.50)
	(medium hard steel)		
BARS	Steel	< 60 daN/mm ² < 42 daN/mm ²	Ø 18 Ø 20
	Copper	< 30 daN/mm ² < 25 daN/mm ²	Ø 30 Ø 32
	Aluminum	< 16 daN/mm ²	Ø 40

* Other dimensions and cables to be approved with tests.



Do not use this tool on live cables.