



**LOCKING PIN**  
Enables security when closing head.




NEOELEC™  
**BPE130**

HYDRAULIC CRIMPING TOOL  
MINI PISTOL TYPE

18V  
2Ah

HEXAGONAL CRIMPING  
6 > 400 mm<sup>2</sup>



> Identical force, stroke and capacities as the C130-xx, XC130-xx and the battery operated tool BPP130x.



**EXCELLENT WEIGHT/CAPACITY RATIO**  
From 6 up to 400 mm<sup>2</sup>.




**STRONG HEAD**  
130 kN



**ROTATIVE HEAD**  
360°

<b>STROKE</b>	12 mm
<b>FORCE</b>	130 kN
<b>CRIMPING TIME</b> (depending on section)	8 to 14 s
<b>BATTERY CAPACITY</b> (for 185 mm <sup>2</sup> copper lug)	50 crimps
<b>DIMENSIONS</b> (L x l x h in mm)	310 x 65 x 300
<b>WEIGHT</b> (with battery)	4.680 kg



Die sets  
6 > 400 mm<sup>2</sup>



**DIE SETS** – Refer to **PAGES 89 – 97.**

> Common interchangeable die sets for C130-xx, XC130-xx, BPE130 & BPP130x tools.

APPLICATIONS	SECTIONS
Copper lugs and sleeves – NFC 20-130	6 > 400 mm <sup>2</sup>
Bare or insulated sleeves in copper or alu. – EDF	E54 > E280
Copper or alu lugs and sleeves – DIN 48083	KZ6 > KZ34
C-shaped connectors	C10 > C70
Pre-rounding die sets	50 > 300 mm <sup>2</sup>
Copper lugs and sleeves – NFC 20-130	10 > 240 mm <sup>2</sup>



<b>DIMENSIONS</b> (mm)	520 x 440 x 130
<b>WEIGHT</b>	2.300 kg

> Case and charger delivered with the tool.  
> **NEOELEC™** accessories  
Refer to **PAGE 56 – 57.**