



PHE706

220V ELECTRICAL HYDRAULIC POWER PACK

> All DUBUIS 700 bar hydraulic heads can be used with this unit.



DESIGNED FOR INTENSIVE USE

- Appropriate for workshop use.
- Possibility to adapt a distributor to use 2 hydraulic heads.



SILENT & POWERFUL MOTOR

Gives an excellent weight/capacity ratio.



HIGH & CONSTANT FLOW

ex. : Crimping of 6 × 185 mm² lugs per minute with a **XC130**.



OIL CAPACITY

- Enables use of hoses > 3 m.
- Filling and draining of the tank accessible.
- Viewing of the oil level.



EMERGENCY BUTTON

Manual release in case of electrical dysfunction.

PRESSURE	700 bar
POWER SUPPLY	220 V – 50 Hz (available in 110 V 50 Hz, or equipped with UK or US plug)
SOUND LEVEL	< 80 dB (A)
OIL TANK	2 L
DIMENSIONS (mm)	380 × 200 × 420
WEIGHT	17 kg (full oil included)

550 W – 220 V – 50 Hz asynchronous motor
Starting up capacitor (enables starting up in load).

Automatic stop at 700 bar

160 mA fuse

Overheat thermal protection

Overpressure mechanical protection

Flow: 0.8 L/min

Protection level: IP 55 according to NF EN 60529



160 mA FUSE

Two extra fuses
> Delivered with the group.



2 SWITCHES REMOTE CONTROL

Advance/Hold – Return
cable length: 3 m
> Delivered with the group.



FITTINGS & HOSES ACCESSORIES

> Refer to **PAGE 66 – 67**.



DIMENSIONS (mm)	600 × 400 × 490
WEIGHT	10.700 kg
PART N°	82132 (delivered separately)
CAPACITY	1 group + 1 hose + 1 hydraulic head + various accessories