




LOCK
Enables quick opening and closing head.

XD62

CRIMPING HYDRAULIC HEAD

700 bar

HEXAGONAL CRIMPING
6 > 300 mm²




> Identical force, stroke and capacities as the hand tool **D62** and the battery operated tools **BPE062**, **BPL062** & **BPP062**.




VERY LIGHT HEAD
Excellent ratio weight/capacities.



COMPATIBLE DIE SETS
With **80 kN** & **130 kN** ranges.



Die sets
6 > 300 mm²



DIE SETS – Refer to **PAGES 88 – 96**.

> Common interchangeable die sets for **D62**, **BPE062**, **BPL062** & **BPP062** tools.

STROKE	13 mm
FORCE	62 kN
DIMENSIONS (L x l x h in mm)	195 x 53 x 100
WEIGHT	2.200 kg

APPLICATIONS	SECTIONS
Copper lugs and sleeves – NFC 20-130	6 > 300 mm
Copper or alu. lugs and sleeves – DIN 48083	KZ6 > KZ34
C-shaped connectors	C10 > C50
Pre-rounding die sets	25 > 240 mm ²
Bare or insulated sleeves in copper or alu.	E54 > E280



FITTINGS & HOSES
> Refer to **PAGE 67**.