

C130-26 NEO XC130-26 NEO

▶ MANUAL HYDRAULIC CRIMPING TOOL



C130-26 NEO SNCF SYMBOL No. 7.393.4957

Hand-pumped hydraulic tool, ideal for crimping, especially overhead lines.

- Very large crimping capacity: 6 to 300 mm².
- C-shaped head with 26 mm opening, rotating through 320°.
- Equipped with a mechanical stop that blocks the piston at the end of its stroke.
- Two-stage hydraulic pump, reducing the number of pumping actions.
- Automatic release with "audible click".
- Piston returns by rotating the moveable handle and then closing.

AS AN OPTION:

- Insulation of the tool body and handles: reducing the risks of short-circuits when used close to non-insulated live switchgear.

▶ Available with stroke of 26, 32, 38 & 44.

XC130-26 NEO SNCF SYMBOL No. 7.393.7550

Crimping head powered by a 700 bar hydraulic power source, ideal for crimping, especially overhead lines.

- Very large crimping capacity: 6 to 300 mm².
- C-shaped head with 26 mm opening.
- Equipped with a mechanical stop that blocks the piston at the end of its stroke.
- Connects to a hydraulic power pack via high pressure hose for intensive or semi-intensive use (depending on the power pack that is used).

AS AN OPTION:

- Remote control support (Part No. 82833) to fit the control handle for the Dubuis hydraulic power pack directly on the XC130 head.

▶ Available with stroke of 26, 32, 38 & 44.

TECHNICAL SPECIFICATIONS

	C130-26 NEO	XC130-26 NEO
FORCE	130 kN	130 kN
STROKE	26 mm	26 mm
DIMENSIONS (mm)	565 × 70 × 160	215 × 70 × 125
WEIGHT	5.270 kg	3.760 kg
HEXAGONAL CRIMPING	6 > 300 mm ²	6 > 300 mm ²

CRIMPING DIE SETS:

- Interchangeable die sets that are common to tools in the 130 kN product line, head, manual, Elec & **NEOELEC™** versions. (see pages 34, 35 and 36)

▶ All our tools are supplied without dies



CASES

	C130-26 NEO	XC130-26 NEO
DIMENSIONS (mm)	680 × 430 × 160	405 × 270 × 105
WEIGHT	3.600 kg	3.120 kg
PART No.	85037 (supplied empty)	30321 (supplied empty)
CAPACITY	Tool + 24 die sets	Crimping head + 5 die sets

CRIMPING CAPACITY

APPLICATION	Copper sleeves and lugs NFC 20.130	Copper or aluminium bare or insulated sleeves EDF	Copper - aluminium sleeves and lugs DIN 48083	"C" connectors	Pre-rounding	Copper sleeves and lugs NFC 20.130
CRIMP SHAPE						
SECTION	6 > 300 mm ²	E54 > E235	KZ6 > KZ28	C10 > C70	50 > 300 mm ²	10 > 240 mm ²